

MATERIAL SAFETY DATA SHEET

INLAND MOTOR SHAFT LUBRICANT

Chemical Name and Synonyms: Lubricant

Part Number/Trade Name: 50022/Motor Shaft Lubricant

DOT Hazardous Classification: DOT regulated grease or oil - N.O.S.

NFPA Health Hazard: 0 Flammability: 1 Reactivity: 0 Personal Protection: B

SECTION I - GENERAL INFORMATION

Manufacturer's Name: Inland Craft Products, Co.

Manufacturer's Street: 32052 Edward

Manufacturer's City: Madison Heights

Manufacturer's State: Michigan

Manufacturer's Zip: 48071

Manufacturer's Emergency Phone: 1-248-583-7150

Manufacturer's Phone: 1-248-583-7150

Date Prepared: 08-07-2007

SECTION II - INGREDIENTS

If present, IARL, NTP and OSHA Carcinogens and chemical subject to this reporting requirements of SARA Title 111. Section 313 are identified in this section

	CAS NUMBER	TLC	PEL	%
(Non Hazardous) Components				
POLYTETRAFLUORETHANE	9002-84-0			
PROPRIETARY COMPONENTS		N.J.T.S.R.N.		
SYNTHETIC OIL		80100362-5008P		85 TO 95
	80100362-5004P			2 TO 5
		80100362-5014P		2 TO 5
		80100362-5049P		01. TO 1.0

SECTION III - PHYSICAL DATA

Boiling Point (° F): N/A

Melting Point (° F): N/A

Vapor Pressure (mm Hg.): N/A

Vapor Density (AIR=1): N/A

Specific Gravity (Water=1): 0.89

Percent Volatile by Volume (%): N/A

Evaporation Rate: N/A

Solubility in Water: Insoluble

Color: Translucent

Appearance and Odor: semi solid, mild odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: (ASTM D92) C.O.C. 400° F

Upper Flammable Limit: N/D

Lower Flammable Limit: N/D

Extinguishing Media: Dry Chemical, Water Fog, Foam Carbon Dioxide

Special Fire Fighting Procedures: Treat as oil fire: Use self contained breathing apparatus

Unusual Fire and Explosion Hazards: None

SECTION V - HEALTH HAZARD DATA

Carcinogens: No carcinogens present

Routes of Entry: Ingestion

Effects of Overexposure: May cause irritation to eyes and skin on sensitive individuals

EMERGENCY FIRST AID PROCEDURES

- EYES: Flush with water for at least 15 minutes
- SKIN: Wash with soap and water. See physician if irritation persists
- INHALATION: Remove to fresh air. See physician if irritation persists
- ORAL: Call a physician. Do not induce vomiting. Keep warm
- ADDITIONAL: Prolonged or repeated contact may produce mild skin irritation and inflammation. personnel with pre-existing skin disorder should avoid contact.

SECTION VI - REACTIVITY DATA

Stability: Stable

Incompatibility (Materials to avoid): Strong oxidizing agents, welding.

Polymerization: Will not occur

Thermal Decomposition Products: Carbon Monoxide, Carbon Dioxide, Trace Fluorene Compounds

Conditions to Avoid: Do not heat above flash point

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Stop flow, scrape, wipe, mop up, or absorb with diatomaceous earth or other inert material. Store in appropriate container for disposal.

Disposal Method: Should be in compliance with federal, state and local laws.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type): Normally not needed

Protective Gloves: Neoprene or nitrile rubber gloves recommended

Eye Protection: Approved safety glasses or goggles

Other Protective Equipment: Chemically resistant boots and apron recommended

Work/Hygienic Practices: Use standard methods

SECTION IX - SPECIAL PRECAUTIONS

Avoid storage near open flame or other sources of ignition. Spills may cause slippery floors. Proper footwear required. Remove contaminated clothing and laundry before reuse. Wash hands with soap and water before eating, drinking or smoking. Discard contaminated leather gloves and shoes.

N/D - Not Determined

N/A - Not Applicable

< - Less Than

> - Greater Than



[MSDS Index](#)